

**YACHTLINE**

# SUPER YACHTLACK

**Code No./colour** MSL .... no. according to colour  
**Gloss** high glossy

**Description** High A quality synthetic enamel characterized by excellent flow, hiding power, chalk and fade resistance, gloss retention and resistance against splash water. Applicable to exterior areas above the water line and interior areas of yachts and boats of metal and wood construction.

**Recommended use** For boats and yachts made of GRP, wood (not teak) and steel on top of recommended primers.

**Product information**

**Solids volume** abt. 65 % (according to colour)  
**Recommended DFT/WFT** 40/60 microns  
**Theoretical coverage** abt. 12,5 m<sup>2</sup>/ltr. at 40 microns, depending on the roughness of the surface and application  
**Specific gravity** abt. 1,0 g/cm<sup>3</sup> (according to colour)  
**Ingredients** Alcyd resin, titanium dioxide, inorganic and organic pigments, inorganic fillers (additives), aliphatic hydrocarbons (white spirit).  
**Mixture** ---  
**Flash point** + 27 °C  
**Storage** abt. 12 months (under normal conditions)

**Application**

**Pot life** ---  
**Method of application** brush, roller or airless spray  
**Tip size** ---  
**Thinner** Wilckens Yacht 1K-Thinner

Drying time	Temperature	+ 20°C
at 65 % relative humidity	Dust dry	3hrs.
	resistant against rain	6 hrs.
	dry	10 hrs.
<b>Overcoatability interval at 20°C/65 % rel. humidity</b>		min. 16 hrs. at 40 microns DFT

During application the temperature of the surface should be at least 3°C above the dew point of the air.

**Applications temperature** + 5°C till + 30°C

**Surface preparation** The surface must be free of rust, mill scale, oil, salt and moisture. Loose old paint has to be removed and blemishes must be mechanically cleaned. Old coatings should be sanded to matt surface before recoating.

**Recommended paint system**

GRP	1 x CR Universalgrund 1 x Yacht Vorlack 1 – 2 x Yacht Vorlack 1 x CR Universalgrund 1 x Yacht Vorlack
Wood (not teak)	
Steel	

**Overcoatability** With same material.

**Generals**

**Safety precautions**

- flammable
- harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
- keep out of the reach of children
- do not empty into drains
- if swallowed, seek medical advice immediately and show this container or label
- use only in well-ventilated areas
- contains 2-butanone oxime, Cobaltbis (2-ethylhexanoate), 2-ethylhexanoic acid zirconium salt, may produce an allergic reaction
- this Product isn't subject of the VOC-Paint Directive (2004/42/EC)

**General remarks**